

## Tags - A927Z

### Temperature Logger UHF Semi-Passive Tag

- EPC C1G2 (ISO18000-6C) Compatible
- Frequency range: 860 MHz ÷ 928 MHz
- Read range: approx. 10m in air (2.5m on metal) @ 2W ERP
- Unique ID plus long EPC code (512 bit)
- Memory capacity: 8000 samples (16 kbyte)
- Programmable sampling interval
- Programmable temperature thresholds
- Battery life: 3 or 5 years
- Temperature range: -20°C to +70°C
- ±0.1°C Accuracy (typical)
- No calibration required
- Dimensions: 130.4x23.4x12.7 mm3
- Battery charge measurement through RF



CAEN RFID's EASY2LOG® Temperature Logger Mod. A927Z is a low cost, semi-passive UHF tag that allows to monitor temperature sensitive products during transportation or storage.

Being compliant to the EPC Class1 Gen2/ISO18000-6C standards, EASY2LOG® can be used with most of the Gen2 UHF RFID readers on the market without requiring any additional equipment.

The Logger is configurable either in Continuous or Over-Threshold logging modes, allowing the storage of up to 8000 temperature samples with programmable sampling times. Once programmed, the tag will start to monitor the life of your temperature sensitive product, thus allowing to identify any problems occurred along the whole cold chain by just performing an inventory cycle.

The EASY2LOG® temperature logger is recommended for recording temperatures during transportation and/or storage of temperature-sensitive goods such as:

- Fresh food (fruit, vegetables)
- Seafood
- Meat and poultry
- Milk-based products
- Frozen food
- Chemical/pharmaceutical products

[Product developed under the BRIDGE FP6 European Funded project](#)



Ordering code

Technical Specifications Table

**WA927ZAAAAAA**

A927 - Temperature logger UHF semi-passive tag(EPC C1G2) Std

<b>Tag type</b>	semipassive
<b>Overall dimensions</b>	130.4 x 23.4 x 12.7 mm <sup>3</sup>
<b>Intended region of operation</b>	EU/US
<b>Reserved memory size</b>	512 bit
<b>EPC memory size</b>	512 bit
<b>TID memory size</b>	208 bit
<b>Reserved memory size</b>	512 bit
<b>User Memory size</b>	17484 byte
<b>Access control</b>	yes
<b>Memory retention</b>	100 years
<b>Memory endurance</b>	10000 cycles
<b>Read range</b>	10 m @ 2W ERP
<b>Frequency band</b>	860 MHz ÷ 930 MHz
<b>Write range</b>	10 m @ 2W ERP
<b>Write time</b>	100 µsec
<b>Operating temperature</b>	-20°C to +70°C
<b>Storage temperature</b>	-20°C to +70°C
<b>Environmental rating</b>	IP65
<b>Temperature Sensor resolution</b>	16 bit
<b>Accuracy</b>	±0.1 °C (typ); ±0.75 °C (max)
<b>Logging memory size</b>	8192 samples
<b>Sampling Time</b>	8 sec (min); 18 Hour (max)

---

© 2010 CAEN RFID Srl - [info@rfid.caen.it](mailto:info@rfid.caen.it)

**CAEN RFID Srl**

Via Vetraia, 11 - 55049 Viareggio (LU) - ITALY  
Tel +39 0584 388 398 - Fax +39 0584 388 959  
<http://www.rfid.caen.it> - e-mail: [info@rfid.caen.it](mailto:info@rfid.caen.it)

